



Jack

Manufacturer:	Houston Energy Service (HES) Pty Ltd
Jack:	Stroke 6' 1" with 4" cylinders and 2.5" rods
Stroke Speed:	Average Full Stroke 10.8 seconds
Jack Pull:	75,000lbs
Snub Force Push:	45,000lbs
Rigged Up Height:	128" bottom of double BOP to top of jacket plate
Interlock System:	Rig Smart™ "Snub Smart" Rig Smart™ "Slip Smart"

Engine

Make:	Duetz
Model:	914 <ul style="list-style-type: none"> • air cooled • 150hp • 6 cylinder diesel

Rotary

PASSIVE ROTARY

Make:	HES
Capacity:	186,000lbs <ul style="list-style-type: none"> • Dual 9 x 14" tapered roller bearings • Positive anti rotational lock incorporated in design

Well Control

ANNULAR TYPE PREVENTER

Make:	Integrated
Model:	ISA <ul style="list-style-type: none"> • 7 1/16" • 5,000psi • Bolted cover, studded top with flanged bottom

RAM TYPE PREVENTER

Make:	Integrated
Model:	IE (Duel Ram) <ul style="list-style-type: none"> • 7 1/16" • 5,000psi • Pipe ram Inserts 2 3/8", 2 7/8", 3 1/2", 4 1/2"

EQUALIZER SYSTEM

Make:	HES
	• 2" Integrated bleed off and equalizing system located on top cavity of Dual Ram BOP, remotely controlled valves from operator panel

ACCUMULATOR

Make:	HES
Capacity:	30 Gallons <ul style="list-style-type: none"> • 3000psi

Lubricator

Size:	7" lubricator in Four (4) x 10' sections
Connections:	9 7/8" - 4x2 Bowen thread connections with a flange for the crossover to BOP 7 1/4" 5K

Ancillary Equipment

Spools:	One (1) x 1' spacer spool with 1/2" NPT side outlet One (1) x 3' spacer spool with 1/2" NPT side outlet
Hot Tap Kit:	5,000psi From 24" to 36" Stroke Available 1/2" - 2" bits
Freeze Unit:	Available on request