







Trailer Manufacturer:

Maxi Trans 45'

Within Queensland Dimensions - not

oversized road train ready

Hydraulic walkways

Walkway access in accordance with

AS1657

Compressor

Manufacturer: Atlas Copco

Model: XRV CD6 2000 Twin Air Compressors

Engine: 2 x CAT C13

Horsepower: 440HP combined total 880HP **Emergency Shut Off:** ESD with ability to tie in **Exhaust:** Fully lagged from manifold

Max Pressure: 365 PSI **Total Actual Free Air:** 1975 CFM

Booster

Manufacturer: Atlas Copco Model: Hurricane B7-41 Caterpillar C7 **Engine:**

Horsepower: 250 HP (186.4 KWH @ 1800 RPM) In-line 6 cyl, 4 stroke diesel **Engine Configuration:**

Emergency Shut Off: Chalwyn Valve **Exhaust:** Completely Lagged Suction: 350 PSI (24.13 BAR) Discharge: 1000 PSI (68.96 BAR) Capacity: 2440 CFM (69m3/min)

Fuel Tank

Capacity: 4,750 litres dual skin

Supplies: Compressor/Booster + 10m transfer hose

with auto shutoff

Advantages

Low fuel burn compared to Sullair

All equipment on 1 trailer

Hydraulic handrails reduce manual handling Guarding around all moving parts as per

AS4042

Integral hard line plumbed in accordance

with AS4041

Weir 2' Fig 1502 adjustable choke and

integral vent stack

Integral condensation belly tank on trailer Full LED lighting complete with Dropsafe nets

for secondary retention

Complete data package supplied

